

Stewart Seeds
2230 E County Road 300 N
Greensburg, Indiana 47240

PLOT FORM



Cooperator B&B Ag-Vantages
Address _____
City Conover
State Ohio Zip _____
Phone _____ Cell _____

Latitude (N) _____
Longitude (W) _____
Corner: NE NW SE SW
County (of plot location) Shelby

Salesperson Kevn Marten
Date Planted 05/20/09
Planting Pop 31,200
Date Harvested 10/27/09

Directions to plot/GPS corner:

PREVIOUS CROP

- CORN
 BEANS
 HAY/ALFALFA
 OTHER

PLOT TYPE

- STRIP
 SIDE BY SIDE
 FIELD CHECK
 REPLICATED

SOIL TEXTURE

- COARSE (sand, loamy sand)
 MEDIUM (silts and loams)
 FINE (clay, silty clay, sandy clay)

WEIGH SYSTEM

- WEIGH WAGON
 YIELD MONITOR
 GRAIN CART SCALE

DRAINAGE

- EXCESSIVE
 GOOD
 MODERATE
 POOR
 VERY POOR

TILLAGE

- NO-TILL
 MIN-TILL
 CONV
 RIDGE
 STRIP/ZONE
 OTHER

WATER

- IRRIGATED
 DRYLAND ARID
(limiting rainfall normally, irrigation is common)
 DRYLAND WET
(adequate rainfall normally, drainage tile is common)

SOIL FERTILITY

- LOW MED HIGH

LBS/ACRE

N:	134	P:	200	K:	50
S:		Zn:			

ORGANIC MATTER

- LOW (<2.0%)
 MED (2.0 - 4.5%)
 HIGH (>4.5%)

SOIL pH

- LOW (<6.0)
 MED (6.0 - 7.5)
 HIGH (>7.5)

Crop Ratio: corn = 109.815 ; soy = 100.138

HERBICIDE(S): _____

INSECTICIDE(S): _____

FUNGICIDE(S): _____

SEED COMPANY	CORN BRAND NUMBER	TRAIT	SEED TREATMENT	HRVST POP.	STALK LODGE %	ROOT LODGE %	100	-	MOIST. %	x	WEIGHT (LBS.)	x	CROP RATIO (see above)	÷	ROW LENGTH (FT.)	÷	ROW WIDTH (IN.)	÷	NO. OF ROWS	=	YIELD BU/ACRE	TEST WT.	COMMENTS
Campbell	599-96	VT3	P250	30K			100	-	28.4	x	1564	x	109.815	÷	600	÷	30	÷	3	=	227.7	58.0	
Stewart	6T546	VT3	P250	30K			100	-	28.0	x	1438	x	109.815	÷	600	÷	30	÷	3	=	210.6	57.0	
Stewart	6T672	VT3	P250	30K			100	-	28.4	x	1528	x	109.815	÷	600	÷	30	÷	3	=	222.5	54.0	
Pioneer	34A20	HXX/RR	P250	30K			100	-	30.8	x	1544	x	109.815	÷	600	÷	30	÷	3	=	217.3	56.0	
Stewart	7V247	VT3PRO	P250	30K			100	-	27.5	x	1568	x	109.815	÷	600	÷	30	÷	3	=	231.2	54.0	
Stewart	7T683	VT3	P250	30K			100	-	30.5	x	1615	x	109.815	÷	600	÷	30	÷	3	=	228.3	56.0	
Stewart	7T618	VT3	P250	30K			100	-	30.7	x	1696	x	109.815	÷	600	÷	30	÷	3	=	239.0	58.0	
Pioneer	33F88	HXX/RR	P250	30K			100	-	34.0	x	1566	x	109.815	÷	600	÷	30	÷	3	=	210.2	57.0	
Stewart	8T339	VT3	P250	30K			100	-	31.8	x	1694	x	109.815	÷	600	÷	30	÷	3	=	234.9	59.0	
Stewart	8T755	VT3	P250	30K			100	-	31.6	x	1432	x	109.815	÷	600	÷	30	÷	3	=	199.2	57.0	
Stewart	8T266	VT3	P250	30K			100	-	31.8	x	1506	x	109.815	÷	600	÷	30	÷	3	=	208.9	57.0	
Stewart	7T630	VT3	P250	30K			100	-	27.6	x	1398	x	109.815	÷	600	÷	30	÷	3	=	205.8	58.0	
							100	-		x		x		÷		÷		÷		=			
							100	-		x		x		÷		÷		÷		=			
							100	-		x		x		÷		÷		÷		=			
TEST AVERAGE																					30.1		
																					219.6	56.8	

TESTIMONIAL / COMMENTS:

Signature: _____

Date: _____