

Stewart Seeds
2230 E County Road 300 N
Greensburg, Indiana 47240

PLOT FORM



Cooperator Dean Thompson
Address _____
City _____
State OH Zip _____
Phone _____ Cell _____

Latitude (N) _____
Longitude (W) _____
Corner: NE NW SE SW
County (of plot location) Darke

Salesperson Kevin Marten
Date Planted 05/02/09
Planting Pop _____
Date Harvested _____

Directions to plot/GPS corner:

PREVIOUS CROP

- CORN
 BEANS
 HAY/ALFALFA
 OTHER

PLOT TYPE

- STRIP
 SIDE BY SIDE
 FIELD CHECK
 REPLICATED

SOIL TEXTURE

- COARSE (sand, loamy sand)
 MEDIUM (silts and loams)
 FINE (clay, silty clay, sandy clay)

WEIGH SYSTEM

- WEIGH WAGON
 YIELD MONITOR
 GRAIN CART SCALE

DRAINAGE

- EXCESSIVE
 GOOD
 MODERATE
 POOR
 VERY POOR

TILLAGE

- NO-TILL
 MIN-TILL
 CONV
 RIDGE
 STRIP/ZONE
 OTHER

WATER

- IRRIGATED
 DRYLAND ARID
(limiting rainfall normally, irrigation is common)
 DRYLAND WET
(adequate rainfall normally, drainage tile is common)

SOIL FERTILITY

- LOW MED HIGH

LBS/ACRE

N:	P:	K:
S:	Zn:	

ORGANIC MATTER

- LOW (<2.0%)
 MED (2.0 - 4.5%)
 HIGH (>4.5%)

SOIL pH

- LOW (<6.0)
 MED (6.0 - 7.5)
 HIGH (>7.5)

Crop Ratio: corn = 109.815 ; soy = 100.138

HERBICIDE(S): _____

INSECTICIDE(S): _____

FUNGICIDE(S): _____

SEED COMPANY	CORN BRAND NUMBER	TRAIT	SEED TREATMENT	HRVST POP.	STALK LODGE %	ROOT LODGE %	100	MOIST. %	WEIGHT (LBS.)	CROP RATIO (see above)	ROW LENGTH (FT.)	ROW WIDTH (IN.)	NO. OF ROWS	YIELD BU/ACRE	TEST WT.	COMMENTS
Stewart	8T339	VT3		32000			100	27.0	1825	109.815	330	36	6	205.2	56.0	
Campbell	692-86	VT3		32000			100	24.0	1735	109.815	330	36	6	203.1	56.0	
Stewart	7T630	VT3		32000			100	24.0	1850	109.815	330	36	6	216.6	56.0	
Stewart	8T266	VT3		32000			100	22.8	1720	109.815	330	36	6	204.6	56.0	
Stewart	8T755	VT3		32000			100	23.2	1770	109.815	330	36	6	209.4	56.0	
Stewart	8T339	VT3		32000			100	25.6	1900	109.815	330	36	6	217.8	56.0	
Pioneer	P33F88	HXX/RR		32000			100	27.1	1850	109.815	330	36	6	207.8	56.0	
Stewart	7T618	VT3		32000			100	24.4	1705	109.815	330	36	6	198.6	56.0	
Stewart	7T683	VT3		32000			100	23.2	1750	109.815	330	36	6	207.1	56.0	
Stewart	7V747	VT3		32000			100	20.8	1550	109.815	330	36	6	189.1	56.0	
Pioneer	P34A20	HXX/RR		32000			100	24.5	1750	109.815	330	36	6	203.6	56.0	
Stewart	6T672	VT3		32000			100	21.8	1810	109.815	330	36	6	218.1	56.0	
Stewart	6T546	VT3		32000			100	22.0	1765	109.815	330	36	6	212.1	56.0	
Stewart	7K456	YGPL/RR		32000			100	23.5	1805	109.815	330	36	6	212.7	56.0	
Stewart	S520R	Conv.		32000			100	27.0	1770	109.815	330	36	6	199.1	57.0	
TEST AVERAGE				32000				24.3						207.2	56.1	

TESTIMONIAL / COMMENTS:

Signature: _____

Date: _____

