

Stewart Seeds
2230 E County Road 300 N
Greensburg, Indiana 47240

PLOT FORM



Cooperator Keith Waris
Address _____
City Kinsman
State OH Zip _____
Phone _____ Cell _____

Latitude (N) _____
Longitude (W) _____
Corner: NE NW SE SW
County (of plot location) Trumbull

Salesperson Bob White
Date Planted 05.08.09
Planting Pop 32,000
Date Harvested 11/23/09

Directions to plot/GPS corner:

PREVIOUS CROP

- CORN
 BEANS
 HAY/ALFALFA
 OTHER

PLOT TYPE

- STRIP
 SIDE BY SIDE
 FIELD CHECK
 REPLICATED

SOIL TEXTURE

- COARSE (sand, loamy sand)
 MEDIUM (silts and loams)
 FINE (clay, silty clay, sandy clay)

WEIGH SYSTEM

- WEIGH WAGON
 YIELD MONITOR
 GRAIN CART SCALE

DRAINAGE

- EXCESSIVE
 GOOD
 MODERATE
 POOR
 VERY POOR

TILLAGE

- NO-TILL
 MIN-TILL
 CONV
 RIDGE
 STRIP/ZONE
 OTHER

WATER

- IRRIGATED
 DRYLAND ARID
(limiting rainfall normally, irrigation is common)
 DRYLAND WET
(adequate rainfall normally, drainage tile is common)

SOIL FERTILITY

- LOW MED HIGH

LBS/ACRE

N: 185 P: 46 K: 120
S: _____ Zn: _____

ORGANIC MATTER

- LOW (<2.0%)
 MED (2.0 - 4.5%)
 HIGH (>4.5%)

SOIL pH

- LOW (<6.0)
 MED (6.0 - 7.5)
 HIGH (>7.5)

Crop Ratio: corn = 109.815 ; soy = 100.138

HERBICIDE(S): Round-up

INSECTICIDE(S): _____

FUNGICIDE(S): _____

SEED COMPANY	CORN BRAND NUMBER	TRAIT	SEED TREATMENT	HRVST POP.	STALK LODGE %	ROOT LODGE %	100	MOIST. %	WEIGHT (LBS.)	CROP RATIO (see above)	ROW LENGTH (FT.)	ROW WIDTH (IN.)	NO. OF ROWS	YIELD BU/ACRE	TEST WT.	COMMENTS	
Campbell	55-23	YGPL/RR		31000			100	19.7	8648	109.815	725	30	16	219.1	57.0		
Stewart	5R341	RR		31400			100	19.5	8798	109.815	725	30	16	223.5	55.0		
Stewart	4T722	VT3		31100			100	19.5	8698	109.815	725	30	16	221.0	54.0		
Campbell	481-76	VT3		30800			100	18.8	8520	109.815	725	30	16	218.3	53.0		
Campbell	588-86	VT3		30500			100	19.5	8638	109.815	725	30	16	219.4	55.0		
Stewart	6T725	VT3		30000			100	19.0	8190	109.815	725	30	16	209.3	53.0		
Stewart	6T546	VT3		30500			100	21.9	8470	109.815	725	30	16	208.7	53.0		
Stewart	6T672	VT3		31000			100	22.2	8934	109.815	725	30	16	219.3	52.0		
Pioneer	34A20	HXX/RR		30000			100	23.7	8718	109.815	725	30	16	209.9	53.0		
Stewart	7V247	VT3		30800			100	22.6	4782	109.815	725	30	8	233.6	52.0		
Stewart	7T683	VT3		31000			100	22.9	4060	109.815	725	30	8	197.6	54.0		
Stewart	7T618	VT3		30500			100	22.3	4316	109.815	725	30	8	211.6	53.0	regular pop.	
Stewart	7T618	VT3		33500			100	23.1	4264	109.815	725	30	8	206.9	52.0	higher pop.	
Stewart	7T630	VT3		31000			100	24.2	4216	109.815	675	30	8	216.6	52.0		
							100										
TEST AVERAGE				30936				21.4							215.4	53.4	

TESTIMONIAL / COMMENTS:

Signature: _____

Date: _____